



Tianbo Foam fire extinguishers provide a cleaner and also same effective alternative to dry powder extinguishers for class A and B fire risks

- ◆ Designed and approved to BS EN3-7
- ◆ All models except TMFM1S are tested to clause 9.2 of EN3-7 for use on live electrical equipments
- ◆ TMFM1S is technical approved to EN3-7 except clause 6.1 which states the minimum charge for water based extinguishers shall be 2Litre
- ◆ High UV resistant polyester coating for extra protection from extremely harsh elements
- ◆ Polyethylene lined cylinders for corrosion resistance
- ◆ Easy squeeze-grip operation and all metal handles
- ◆ Complete with metal brackets (1, 2Litre models with vehicle brackets).
- ◆ Heavy duty brackets for marine and truck applications are optional



CE BS EN3-7 

## Technical Data

Model	TMFM1S	TMFM2S	TMFM3S	TMFM6S	TMFM9S
Propellant Type	Store Pressure				
Extinguishing Medium	AFFF Foam	AFFF Foam	AFFF Foam	AFFF Foam	AFFF Foam
Capacity (Litre)	1	2	3	6	9
Height(mm)	335	403	438	537	620
Shell Diameter(mm)	85	110	130	162	182
Working Pressure(bar)	15				
Test Pressure(bar)	27				
Full Weight(kg)	1.90	3.60	5.20	9.60	14.00
Discharge Time Approx.(second)	8	15	20	22	30
Temperature Range	5°C-+60°C	5°C-+60°C	5°C-+60°C	5°C-+60°C	5°C-+60°C
Fire Rating	5A 34B	8A 55B	13A 89B	21A 144B	27A 233B
Approved to BS EN3-7	√	√	√	√	√